

110300656211 120503

9469.0-01 (1856-19700)

Express Mail Label EL 921453434 US

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
APPLICATION FOR UNITED STATES LETTERS PATENT**

**Redundant Seal Design for Composite Risers with Metal Liners**

**By:**

**Mamdouh M. Salama  
2505 Wildwood Ave.  
Ponca City, OK 74604  
Citizenship: USA**

55638 01/1856 19700

**TITLE**

Redundant Seal Design for Composite Risers with Metal Liners.

**CROSS-REFERENCE TO RELATED APPLICATIONS**

Not applicable.

**STATEMENT REGARDING FEDERALLY SPONSORED  
RESEARCH OR DEVELOPMENT**

Not applicable.

**REFERENCE TO A MICROFICHE APPENDIX**

Not applicable.

**FIELD OF THE INVENTION**

[0001] The present invention relates to redundant sealing systems for composite risers having metal liner assemblies and methods of preventing interior fluid leakage to the outside of metal lined composite risers. More particularly, the present invention relates to an elastomeric tip provided on a metal to composite interface of the metal liner assembly and integrated with an outer elastomeric ply provided over the liner assembly which, in combination with a mechanical seal between the metal to composite interface and a transition ring of the liner assembly, provides a dual sealing system for the composite riser to prevent leakage of interior fluids.

**BACKGROUND OF THE INVENTION**

[0002] As exploration and production of oil and gas move into deeper water, weight, cost and reliability of water-depth sensitive systems such as risers become increasingly important. The term riser generally describes the different types of discrete pipes that extend from the seabed toward the surface of the water. These include components such as drilling risers, production risers, workover risers, catenary risers, production tubing,

production risers, choke and kill lines and mud return lines. Risers can be constructed of metal and, more particularly, of steel. More recently, composite risers are being considered.

[0003] The advantages that composites offer to deepwater risers are high specific strength and stiffness, lightweightedness, corrosion resistance, high thermal insulation, high damping, and excellent fatigue performance. Capitalizing on these and other advantages for composite riser applications can result in lower system cost and higher reliability for deepwater developments. Efforts have been devoted during the recent years to assess the full potential of composite materials for deepwater riser applications. The cost savings and enabling capability of composite risers for deepwater drilling and production operations are particularly appealing.

[0004] Conventional composite risers are constructed of an outer composite material and an inner liner assembly. More particularly, in a conventional composite riser, a thin tubular metal or elastomeric liner is coaxially secured to the metal connections to form the liner assembly. For a liner assembly comprising a metal liner, an elastomeric shear ply is provided along the outer surface of the liner assembly, followed with a composite overwrap reinforcement to form the composite riser. The composite riser is heated to cure the elastomeric shear ply and the composite overwrap. An external elastomeric jacket and a layer of composite overwrap are provided over the composite riser and thermally cured for external damage and impact protection to the composite riser. The liner assembly is necessary to prevent leakage due to the inherent cracking characteristics of the composite material. The matrix in the composite will develop micro cracks at pressures lower than those at which the composite fibers will fail. The matrix micro

cracking is due to the thermal stresses induced by the curing cycle and the mechanical stresses induced during the shop acceptance pressure test of the composite riser during the manufacturing process. Thus, liner assemblies are essential in ensuring fluid tightness of composite risers to prevent leakage under the conditions of matrix cracking which is inevitable.

[0005] The integrity of the composite riser, particularly at the interface between the composite overwrap and the metal connector of the liner assembly, presents a reliability issue for composite risers. Composite risers with elastomeric liners have a seal at the termination between the metal connector and elastomeric liner which is formed by the bonding of the elastomeric material of the liner and an elastomeric material which is provided on the tip of the metal termination. The reliability of the sealing system is questionable, particularly given that environmental degradation occurs to the elastomers by the production fluids.

[0006] While elastomeric liners are acceptable for production composite risers, they are ill suited for use in composite drilling or workover risers. The likely possibility of damage to elastomeric liners by the mechanical tools which are required for drilling and workover operations make the elastomeric liners undesirable for these types of operations. Thus, metal liners for composite drilling and workover risers are being considered. Metal liners also have applications as composite production risers as the metal offers better long term resistance to the production fluids than elastomers. In a conventional composite riser having a metal liner, the metal liner is welded directly to the metal connector at a section called the metal to composite interface (MCI). Alternatively, the metal liner is coaxially secured to the MCI through the use of a transition ring. The

transition ring is secured at one end to the MCI and is welded at the other end to the metal liner. An advantage of using a transition ring is its ability to serve as a transition between the material of the liner and that of the MCI when different grade materials are required. For example, a liner and transition ring can be constructed of titanium, while steel can be used for the MCI. The integrity of the composite riser is dominated by the fatigue resistance of the liner welds, including the weld between the liner and the MCI or the weld between the liner and the transition ring. In addition, the seal between the transition ring and the MCI is critical to the fluid tightness of the composite riser assembly.

#### SUMMARY OF THE INVENTION

[0007] The present invention provides redundant sealing systems for a composite riser having a metal liner which is mechanically secured to a metal-to-composite interface (MCI) through a transition ring, and methods of preventing interior fluid leakage to the outside of metal lined composite risers.

[0008] An elastomeric seal is provided between the MCI and an elastomeric shear ply provided on the outside of the metal liner assembly of the composite riser. The elastomeric seal, in combination with a mechanical seal between the MCI and transition ring, provides a dual seal between the MCI and the metal liner to prevent leakage of interior fluids to the outside of the composite riser. In the event that the integrity of the mechanical seal or the weld between the liner and transition ring is compromised, the elastomeric seal would prevent leakage of internal fluids.

[0009] The elastomeric seal comprises an elastomeric tip which is applied in an uncured state to an inboard end of the MCI and which extends along a portion of the

[illegible]

1871-1872 - 1873-1874 - 1875-1876 - 1877-1878 - 1879-1880 - 1881-1882 - 1883-1884 - 1885-1886 - 1887-1888 - 1889-1890 - 1891-1892 - 1893-1894 - 1895-1896 - 1897-1898 - 1899-1900 - 1901-1902 - 1903-1904 - 1905-1906 - 1907-1908 - 1909-1910 - 1911-1912 - 1913-1914 - 1915-1916 - 1917-1918 - 1919-1920 - 1921-1922 - 1923-1924 - 1925-1926 - 1927-1928 - 1929-1930 - 1931-1932 - 1933-1934 - 1935-1936 - 1937-1938 - 1939-1940 - 1941-1942 - 1943-1944 - 1945-1946 - 1947-1948 - 1949-1950 - 1951-1952 - 1953-1954 - 1955-1956 - 1957-1958 - 1959-1960 - 1961-1962 - 1963-1964 - 1965-1966 - 1967-1968 - 1969-1970 - 1971-1972 - 1973-1974 - 1975-1976 - 1977-1978 - 1979-1980 - 1981-1982 - 1983-1984 - 1985-1986 - 1987-1988 - 1989-1990 - 1991-1992 - 1993-1994 - 1995-1996 - 1997-1998 - 1999-2000 - 2001-2002 - 2003-2004 - 2005-2006 - 2007-2008 - 2009-2010 - 2011-2012 - 2013-2014 - 2015-2016 - 2017-2018 - 2019-2020 - 2021-2022 - 2023-2024 - 2025-2026 - 2027-2028 - 2029-2030 - 2031-2032 - 2033-2034 - 2035-2036 - 2037-2038 - 2039-2040 - 2041-2042 - 2043-2044 - 2045-2046 - 2047-2048 - 2049-2050 - 2051-2052 - 2053-2054 - 2055-2056 - 2057-2058 - 2059-2060 - 2061-2062 - 2063-2064 - 2065-2066 - 2067-2068 - 2069-2070 - 2071-2072 - 2073-2074 - 2075-2076 - 2077-2078 - 2079-2080 - 2081-2082 - 2083-2084 - 2085-2086 - 2087-2088 - 2089-2090 - 2091-2092 - 2093-2094 - 2095-2096 - 2097-2098 - 2099-2100 - 2101-2102 - 2103-2104 - 2105-2106 - 2107-2108 - 2109-2110 - 2111-2112 - 2113-2114 - 2115-2116 - 2117-2118 - 2119-2120 - 2121-2122 - 2123-2124 - 2125-2126 - 2127-2128 - 2129-2130 - 2131-2132 - 2133-2134 - 2135-2136 - 2137-2138 - 2139-2140 - 2141-2142 - 2143-2144 - 2145-2146 - 2147-2148 - 2149-2150 - 2151-2152 - 2153-2154 - 2155-2156 - 2157-2158 - 2159-2160 - 2161-2162 - 2163-2164 - 2165-2166 - 2167-2168 - 2169-2170 - 2171-2172 - 2173-2174 - 2175-2176 - 2177-2178 - 2179-2180 - 2181-2182 - 2183-2184 - 2185-2186 - 2187-2188 - 2189-2190 - 2191-2192 - 2193-2194 - 2195-2196 - 2197-2198 - 2199-2200 - 2201-2202 - 2203-2204 - 2205-2206 - 2207-2208 - 2209-2210 - 2211-2212 - 2213-2214 - 2215-2216 - 2217-2218 - 2219-2220 - 2221-2222 - 2223-2224 - 2225-2226 - 2227-2228 - 2229-2230 - 2231-2232 - 2233-2234 - 2235-2236 - 2237-2238 - 2239-2240 - 2241-2242 - 2243-2244 - 2245-2246 - 2247-2248 - 2249-2250 - 2251-2252 - 2253-2254 - 2255-2256 - 2257-2258 - 2259-2260 - 2261-2262 - 2263-2264 - 2265-2266 - 2267-2268 - 2269-2270 - 2271-2272 - 2273-2274 - 2275-2276 - 2277-2278 - 2279-2280 - 2281-2282 - 2283-2284 - 2285-2286 - 2287-2288 - 2289-2290 - 2291-2292 - 2293-2294 - 2295-2296 - 2297-2298 - 2299-2300 - 2301-2302 - 2303-2304 - 2305-2306 - 2307-2308 - 2309-2310 - 2311-2312 - 2313-2314 - 2315-2316 - 2317-2318 - 2319-2320 - 2321-2322 - 2323-2324 - 2325-2326 - 2327-2328 - 2329-2330 - 2331-2332 - 2333-2334 - 2335-2336 - 2337-2338 - 2339-2340 - 2341-2342 - 2343-2344 - 2345-2346 - 2347-2348 - 2349-2350 - 2351-2352 - 2353-2354 - 2355-2356 - 2357-2358 - 2359-2360 - 2361-2362 - 2363-2364 - 2365-2366 - 2367-2368 - 2369-2370 - 2371-2372 - 2373-2374 - 2375-2376 - 2377-2378 - 2379-2380 - 2381-2382 - 2383-2384 - 2385-2386 - 2387-2388 - 2389-2390 - 2391-2392 - 2393-2394 - 2395-2396 - 2397-2398 - 2399-2400 - 2401-2402 - 2403-2404 - 2405-2406 - 2407-2408 - 2409-2410 - 2411-2412 - 2413-2414 - 2415-2416 - 2417-2418 - 2419-2420 - 2421-2422 - 2423-2424 - 2425-2426 - 2427-2428 - 2429-2430 - 2431-2432 - 2433-2434 - 2435-2436 - 2437-2438 - 2439-2440 - 2441-2442 - 2443-2444 - 2445-2446 - 2447-2448 - 2449-2450 - 2451-2452 - 2453-2454 - 2455-2456 - 2457-2458 - 2459-2460 - 2461-2462 - 2463-2464 - 2465-2466 - 2467-2468 - 2469-2470 - 2471-2472 - 2473-2474 - 2475-2476 - 2477-2478 - 2479-2480 - 2481-2482 - 2483-2484 - 2485-2486 - 2487-2488 - 2489-2490 - 2491-2492 - 2493-2494 - 2495-2496 - 2497-2498 - 2499-2500 - 2501-2502 - 2503-2504 - 2505-2506 - 2507-2508 - 2509-2510 - 2511-2512 - 2513-2514 - 2515-2516 - 2517-2518 - 2519-2520 - 2521-2522 - 2523-2524 - 2525-2526 - 2527-2528 - 2529-2530 - 2531-2532 - 2533-2534 - 2535-2536 - 2537-2538 - 2539-2540 - 2541-2542 - 2543-2544 - 2545-2546 - 2547-2548 - 2549-2550 - 2551-2552 - 2553-2554 - 2555-2556 - 2557-2558 - 2559-2560 - 2561-2562 - 2563-2564 - 2565-2566 - 2567-2568 - 2569-2570 - 2571-2572 - 2573-2574 - 2575-2576 - 2577-2578 - 2579-2580 - 2581-2582 - 2583-2584 - 2585-2586 - 2587-2588 - 2589-2590 - 2591-2592 - 2593-2594 - 2595-2596 - 2597-2598 - 2599-2600 - 2601-2602 - 2603-2604 - 2605-2606 - 2607-2608 - 2609-2610 - 2611-2612 - 2613-2614 - 26

**[0012]** The elastomeric seal operates in conjunction with the mechanical seal formed by the conforming grooves of the transition ring and the MCI to provide a dual sealing system for the composite metal lined riser. Fluid which flows through the composite riser is prevented from leaking to the outside of the composite riser by the elastomeric

**SUBJECTS**

[REDACTED]

**[0020]** FIGURE 8 is a quarter-sectional view of the composite riser.

**[0021]** FIGURE 1 is a schematic of a conventional offshore drilling and production assembly 10 which illustrates the context of the present invention. An offshore platform 20 supports derrick 24 which is a conventional apparatus for drilling or working over a borehole and producing hydrocarbons from the borehole. Offshore platform 20 is

supported by pontoons 22. A subsea platform 30 is provided on the floor of the sea 32 and a borehole 34 extends downward from the sea floor 32.

[0022] A conventional elongated riser 40 extends between borehole 34 and platform 20. Riser 40 generally comprises a tieback connector 42 proximate borehole 34 and riser sections 44 which extend between platforms 20 and 30 and are connected thereto by flex or taper joints 46 and telescoping section 48. Flex joints 46 and telescoping joint 48 accommodate the movement of platform 20 relative to subsea platform 30 and borehole 34. The elongated riser sections 44 which comprise conventional riser 40 are coaxially secured together. Each riser section 44 must accommodate the pressure of the fluid or gas within the section, the tensile load which is caused by the suspension of additional riser sections 44 below the section, the tensioner load and the bending moments imposed by the relative movement of the platform 20 with respect to the subsea platform 30.

[0023] In a composite riser, metal connectors are coaxially secured to liners to form a liner assembly which is wrapped with an elastomeric shear ply, a composite overwrap reinforcement, an external elastomeric jacket and an outerwrap for impact and external damage protection. The composite overwrap consists of small diameter fibers (6 to 10 microns) of high strength and modulus embedded in a polymer matrix material, e.g., resins or glues. The resin materials have bonded interfaces which capture the desirable characteristics of both the fibers and the matrix. The fibers carry the main load in the composite material while the matrix maintains the fibers in the preferred orientation. The matrix also acts to transfer load into the fibers and protects the fibers from the surrounding environment. The composite material properties depend upon the two major components, the fibers and the polymeric matrix. Commonly known thermoset or



$\frac{1}{2} \left( \frac{1}{2} + \frac{1}{2} \right) = \frac{1}{2}$

187

55638 01/1856 19700

[0026] In liner assembly 105, a tubular transition ring 270 is coaxially secured at one end to inboard end 232 of MCI 230. The other end of transition ring 270 is secured to liner section 110. Transition ring 270 can be coaxially secured by welding its ends to inboard end 232 of MCI 230 and liner section 110 or, alternatively, can be fabricated from a continuous tubular joint with MCI 230 or with liner section 110.

[0027] FIGURE 4 shows a conventional composite riser 100. MCI 230 comprises a plurality of outer grooves 234 which are illustrated in a trap lock configuration. While four trap lock grooves 234 are shown, the number can vary as appropriate for the particular use. In addition, configurations other than a trap lock configuration are acceptable. Each groove 234 is a mechanical interlock joint which is fabricated into the outer surface of MCI 230. An elastomeric shear ply 300 in an uncured state is applied to the outer surface of the liner assembly 105 of FIGURE 2 to provide an interface between the liner assembly 105 and a structural composite overwrap 400. Elastomeric shear ply 300 can have any suitable thickness, and the thickness can vary at particular regions of the liner assembly 105 to achieve desired characteristics. By way of example and not by way of limitation, the thickness of the elastomeric shear ply 300 can be approximately 0.09 inches over the entire length of the liner assembly, while the shear ply thickness can be reduced to approximately 0.01 inches over outer grooves 234 of MCI 230. A thinner elastomeric shear ply interface over outer grooves 234 allows the surface of the grooves 234 and the shear ply 300 to move relative to the structural composite overwrap 400.

[0028] Structural composite overwrap 400 is a composite tube comprising carbon, glass or other reinforcing fibers and an epoxy matrix, as previously discussed, which is fabricated over liner assembly 105 using a filament winding process. Generally, the

[illegible]

THE

55638 01/1856 19700

length of the resulting composite riser 100 to prevent migration of seawater into the composite wall and through its interface with the MCI. External elastomeric jacket 500 provides external damage protection and a degree of impact protection, mitigating damage from small dropped objects and mishandling of composite riser 100. A composite of E-glass or other reinforcing fibers such as carbon in a polymeric matrix 600 can be filament wound over the external elastomeric jacket 500 to compact the jacket during the cure and to provide scuff protection. The composite riser is then heated to a suitable temperature to cure elastomeric external jacket 500 and scuff protection outerwrap 600.

[0031] Referring to the quarter-sectional view of MCI 230 shown in FIGURE 5, a first lip 250 and a second lip 260 are provided circumferentially along the inner tubular surface of MCI 230. Second lip 260 is positioned between first lip 250 and inboard end 232 of MCI 230. Second lip 260 defines elastomeric seal surface 262 which extends along the inner tubular surface of MCI 230 from second lip 260 to inboard end 232. First lip 250 defines mechanical seal surface 252 extending along the inner tubular surface of MCI 230 between first lip 250 and second lip 260. A plurality of inner grooves 254 is provided circumferentially along mechanical seal surface 252. Each groove 254 is a mechanical interlock joint which is machined, wound or otherwise fabricated in the inner tubular surface of MCI 230. While grooves 254 are illustrated in a Talon configuration, other configurations common in the art are acceptable.

[0032] Referring to FIGURE 6, an elastomeric tip 264 in an uncured state is applied to inboard end 232 of MCI 230. Elastomeric tip 264 extends along the outer surface of MCI 230 around the tip of inboard end 232 and along elastomeric seal surface 262 to abut

second lip 260. Elastomeric tip 264 is preferably molded to inboard end 232, but can be applied by other fabrication methods. The thickness of elastomeric tip 264 along seal surface 262 should be substantially similar to the depth of second lip 260 into inner surface of MCI 230 such that the elastomeric layer along elastomeric seal surface 262 is substantially flush with mechanical seal surface 252.

[0033] Turning to FIGURE 7, a tubular transition ring 270 having outer grooves 274 which conform to inner grooves 254 of mechanical seal surface 252 of MCI 230 is fitted into inboard end 232 of MCI 230, one end seating against first lip 250 and the other end extending outwardly from inboard end 232. Conforming outer grooves 274 of transition ring 270 and inner grooves 254 of mechanical seal surface 252 engage to form mechanical seal 272 between the inner surface of MCI 230 and the outer surface of transition ring 270. Elastomeric tip 264 engages with transition ring 270 proximate elastomeric seal surface 262. A liner section 110 is secured to transition ring 270 proximate transition ring inboard end 276. Transition ring 270 and liner section 110 can be secured by welding them together coaxially or, alternatively, by fabricating them from a continuous tubular section.

[0034] Referring to the embodiment shown in FIGURE 8 and the previous discussion with reference to FIGURE 4, elastomeric shear ply 300 is applied over the entire length of the outer surfaces of liner section 110, transition ring 270, elastomeric tip 264 and MCI 230. Structural composite overwrap 400 is wound over the elastomeric shear ply 300 as previously discussed and the resulting composite riser 100 is heated to cure the composite overwrap 400, the elastomeric shear ply 300 and the elastomeric tip 264. The

elastomeric shear ply 300 and elastomeric tip 264 bond together along their interface to form elastomeric seal 266.

[0035] After the composite riser 100 is cured, external jacket 500 of an uncured elastomeric material is applied over the entire length of composite riser 100, followed with a filament winding of reinforcing fibers in a polymeric matrix 600. The assembly is heated to a suitable temperature to cure elastomeric external jacket 500 and polymeric matrix 600 thereby providing protection of the composite riser from external damage and impact protection.

[0036] Elastomeric seal 266 provides a second or dual seal for composite riser 100, in addition to the mechanical seal formed between the conforming inner and outer grooves 254, 274 of MCI 230 and transition ring 270, respectively. Elastomeric seal 266 and mechanical seal 272 prevent fluids or gases within the composite riser 100 from leaking to the outside. However, in the event that the integrity of mechanical seal 272 or the liner assembly 105 is compromised, or the weld between the liner and transition ring fails, elastomeric seal 266 would prevent fluid from leaking to the outside of composite riser 100. For example, in composite risers where the weld between transition ring 270 and liner section 110 fails or mechanical seal 272 fails, fluids or gases within liner assembly 105 would migrate through the failed weld or mechanical seal 272 and under elastomeric shear ply 300. The pressure of the leaked fluid or gases would force elastomeric tip 264 against elastomeric seal surface 262 of MCI 230 which would minimize or prevent the fluids or gases from escaping around elastomeric seal 266 to the outside of the composite riser 100. Thus, the use of elastomeric seal 266 in a composite riser would increase the reliability of the sealing system and provide additional time to retrieve and repair the

ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED

THE UNIVERSITY OF CHICAGO